



Technical datasheet

24-08-2012

Product information

Fast Flash® is an environmentally friendly and extremely flexible flashing material which is fast and easy to work with thanks to the self-adhesive back side. Fast Flash® has an infinite number of uses, on the roof where a fast and reliable flashing solution is required.

General specifications

Fast Flash® is a composite material consisting of a stretchable aluminium grid, embedded in a silane-modified polymer rubber with a butyl coating on the back side.

Thickness 2.3 mm - -0.1 - +0.3 mm (*)
Density 1348 kg/m³, equivalent to 3.1 kg/m²
Dimensions Rolls 280, 370, 560 and 1000 mm wide, 5000 mm long
Colours Fast Flash® comes in three standard colours; grey, black or tile red.

(*) The sheets are measured using a thickness gauge, 16 hours after production. It should be noted that the sheet thickness changes easily when worked with.

Technical specifications

Temperature Durable at temperatures between -40°C and +90°C
UV and ozone Fast Flash® is UV and ozone proof
Weather proof Ageing resistant and weather proof
Solubility Insoluble in water
Tightness Fast Flash® is water tight
Guarantee 10 years replacement guarantee according to specified guarantee provisions

OBS! If water travels from copper or bitumen onto Fast Flash®, FlashSeal must be applied to the Fast Flash® surface. If you do not follow the instructions, the warranty becomes void!

Safety and environment

Health hazard class None
Fire hazard class Polymer: None
Aluminium: None.
Butyl: M1 (UNE 23727:1990 – UNE 23721:1990)
Ecolabelling Polymer: MAL* code 00-1 (component A) and 1-1 (component B (1993)
(*Regulation for the labeling concerning inhalation hazards)
Aluminium: Highly environmentally friendly material – no ecolabelling
Butyl: No ecolabelling